

上汽大通V90斗式工程车配置表							
车型名称		斗式工程车					
		加长高顶					
配置信息	座位数		9	12	12	13	13
	指导价 (万元)		25.48	25.48	27.28	25.48	27.28
	轴距 (mm)		3760				
	外形尺寸:长x宽x高 (mm)		5940x2110x2525				
	货斗尺寸:长x宽x高 (mm)		1700X1800x600	1700X1800x600	1700X1800x600	1150x1800x600	1150x1800x600
	总质量 (kg)		4000	4250			
	整备质量 (kg)		2795	2720		2770	
	发动机	型式	上汽π柴油发动机: 四缸16气门, 双EGR, 双轴平衡系统, 双独立冷却循环, 变排量机油泵, 变涡流比				
		排量 (ml)	1996				
		国六排放	●				
		额定功率 (kW/rpm)	6MT: 110/3500 8AT: 130/3500				
		最大扭矩 (N.m/rpm)	6MT: 375/1500~2400 8AT: : 420/1500~2600				
	变速箱		6MT	6MT	8AT	6MT	8AT
	驱动形式		后驱				
	后轮胎形式		双胎				
	最高车速 (km/h)		145				
	燃油箱容积 (L) /尿素罐容积 (L)		80/20				
	制动系统		前/后盘式制动				
	悬架系统		前麦弗逊式独立悬架/后非独立悬架				
	后悬架钢板弹簧片数		3片簧 (加强型)				
	轮胎规格		195/75R16LT				
	车身结构		承载式车身				
	门数		3				
	最小离地间隙 (mm)		210				
外观与内饰							
自动感应LED大灯 (前大灯+后尾灯) +LED日间行		○	○	○	○	○	
前后雾灯		●	●	●	●	●	
右侧移门		●	●	●	●	●	
万力轮胎		●	●	●	●	●	
一体式后踏步		●	●	●	●	●	
后窗灰色隐私玻璃		●	●	●	●	●	
黑色织物座椅		●	●	●	●	●	
大功率冷暖前空调+后单冷后空调+后暖风		●	●	●	●	●	
安全操控							
ABS+EBD+BAS		●	●	●	●	●	
ESP+HHC		●	●	●	●	●	
ASR/TCS牵引力控制系统		●	●	●	●	●	
TPMS胎压监测		○	○	○	○	○	
后倒车雷达		●	●	●	●	●	
前雷达		○	○	○	○	○	
高清倒车影像		●	●	●	●	●	
驾驶座安全气囊		●	●	●	●	●	
副驾驶安全气囊		○	○	○	○	○	
驾驶员安全带未系报警		●	●	●	●	●	
乘客座椅安全带未系报警		○	○	○	○	○	
全车座椅三点式安全带		●	●	●	●	●	
BSD/BSA盲区监测+LCA智能变道辅助		○	○	○	○	○	
舒适便利							
电动调节带加热外后视镜 (集成转向灯)		●	●	●	●	●	
前排电动窗		●	●	●	●	●	
主副驾一键升降+蓝牙来电自动升窗		○	○	○	○	○	
多功能方向盘+蓝牙+定速巡航		●	●	●	●	●	
驻车加热系统		○	○	○	○	○	
感应型自动落锁 (20km/h)		●	●	●	●	●	
熄火自动开锁+内中控锁+自动关闭前照灯		●	●	●	●	●	
折叠遥控钥匙		●	●	●	●	●	
同平面推拉窗 (右移门及对称左侧窗共2扇)		○	○	○	○	○	
尾门180°开度及限位		●	●	●	●	●	
8向可调主驾座椅		●	●	●	●	●	
后排乘客靠背可调节一体式航空座椅		●	●	●	●	●	
高清触控大屏+手机互联+4.2吋液晶仪表+蜘蛛智联		●	●	●	●	●	
视频监控一体机 (GPS&北斗双横行驶记录仪+视频监控)		○	○	○	○	○	
卫星定位系统/行驶记录仪		●	●	●	●	●	
科技网联							
蜘蛛智联(APP)+智慧出行		○	○	○	○	○	
智能安全包 (定速巡航+AEB自动紧急制动+LDW)		○	○	○	○	○	
专用配置							
车顶行李架、登顶梯		○	○	○	○	○	
车顶行李架 (铝板通道)、登顶梯		○	○	○	○	○	

注： ●：为标配； /：为不提供此配置； ○：为选配